Previous Doc First Hit

Next Doc Go to Doc#

Generate Collection **Print**

L4: Entry 142 of 206

File: JPAB

May 28, 1982

PUB-NO: JP357085953A

DOCUMENT-IDENTIFIER: JP 57085953 A

TITLE: CARBIDE DISPERSION TYPE SINTERED IRON ALLOY WITH SUPERIOR WEAR RESISTANCE

PUBN-DATE: May 28, 1982

INVENTOR-INFORMATION:

NAME

COUNTRY

IIJIMA, MASAYUKI AKUTSU, HIDETOSHI ANZAI, KATSUAKI

US-CL-CURRENT: 75/246

INT-CL (IPC): C22C 38/26; C22C 38/38; C22C 33/02

ABSTRACT:

PURPOSE: To enhance the wear and scuffing resistances of the resulting titled alloy by providing a composition consisting of C, Cr, Mn, one or more among P, B and Si, one or more among Zr, Hf, Nb and Ta, and the balance Fe.

CONSTITUTION: This carbide dispersion type sintered Fe alloy has a composition consisting of, by wt., $0.5 \sim 3\%$ C, $5 \sim 20\%$ Cr, $0.05 \sim 5.0\%$ one or more among P, B and $\underline{\text{Si}}$, 0.05~3.0% Mn, 0.05~10.0% one or more among Zr, Hf, Nb and Ta, and the balance Fe with inevitable impurities or further contg. $0.5 \sim 10.0\%$ Mo and/or W and/or $0.5 \sim 10.0$ % one or more among Ni, Co and Cu. This sintered alloy has superior wear, scuffing and pitting resistances and does not damage the opposite member.

COPYRIGHT: (C) 1982, JPO&Japio

Previous Doc Next Doc Go to Doc#